

# tesa® 52060 BigFoam

Foam plate mounting tape for flexographic printing

## PRODUCT INFORMATION

#### **Product Description**

tesa® 52060 Softprint BigFoam is a 1500µm double-coated foam tape designed specifically for mounting photopolymer plates in wideweb film and paper flexographic printing.

Due to its medium hardness foam it is particularly suited for high quality combination of half-tone and solid work.

tesa® Softprint BigFoam offers the following benefits:

- tesa® Softprint BigFoam is highly compressible and therefore offers improved print quality and higher running speeds
- · tesa® Softprint's BigFoam unique construction ensures that print quality is maintained even on extended print runs
- The special adhesive ensures simple mounting, easy repositioning, and demounting of plate and tape without residues
- · During printing a very good bond of tape and plate is achieved. Plates stay securely in place no edge lifting and no plate movement
- The structured PP-liner prevents the formation of air pockets when plate mounting

### **Main Application**

tesa® 52060 Softprint BigFoam is a 1500µm (60 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates in wide-web film and paper flexographic printing.

#### **Technical Data**

- Backing material PF foam Type of liner
- Hardness Thickness category 1500 µm medium Type of adhesive acrylic

For latest information on this product please visit http://l.tesa.com/?ip=52060

Page 1 of 1 / As of 11/03/13

PP

http://www.tesa.com

# tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Phone: +65 (68) 612 026

# tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.